AI Pedestrian Detection Camera



SHB-20XX0T



SHB-20XX0T

2MP AI Pedestrian Detection Camera



Key Features

- 2MP resolution CMOS Sensor
- 2.3mm, 6mm lens options
- True Day/Night with IRC
- 120dB Wide Dynamic Range
- No External Controller Needed
- Web page Calibration via Wi-Fi Hotspot
- Weatherproof IP69K

Ordering Information

SHB-20600T/RL 2MP 6mm AI Pedestrian Detection T D/N Vertical Sideview

SHB-20230T 2MP 2.3mm AI Pedestrian Detection T D/N Horizontal View

SHB-20600T 2MP 6mm AI Pedestrian Detection T D/N Horizontal View AC575 Wi-Fi Hotspot calibration Tool

Illustrations







Whilst every effort has been made to ensure the accuracy of the information provided, no liability can be undertaken for any errors or omissions. All dimensions stated in this document are approximate. Stortech Electronics Ltd reserves the right to alter the specifications and introduce changes without prior notice. © Stortech Electronics 2023

Specifications

SHB-20XX0T

VIDEO	
Imaging Device	1/2.9" Colour CMOS Sensor
Resolution	2MP AHD
Min. Illumination	Colour: 0.01 Lux @ F1.2 / Monochrome 0.0Lux
Video Output	1 V pk-pk 75Ω
Frame Rate	25fps (PAL)/30fps (NTSC)
Gain	Auto
White Balance	Auto
BLC	Yes
Wide Dynamic Range	120db
S/N Ratio	50db (AGC off)
LENS	
Focal Length	2.3 mm, 6mm
Field of View (H x V)	2.3mm: 140 ° / 6mm: 52 °
Lens / Mount Type	Fixed Iris / Board-in type
ALARM SETTINGS	Full-functional
Audible Alarm	Integrated 360AVM algorithm for panoramic images
Audible Volume	Supported 512GB max - up to 133 hrs video recording
Alarm Output	1 x Built-in
Audio Inputs	4 x One-way inputs
Speaker Output	1W / 8Ω
Volume Control	± Power On/Off
Alarm Triggers	5 Separate Triggers
Video Connections	RCA / 4pin connector (Optional)
ENVIRONMENTAL	
Operating Temp/Hum	-20°C ~ +70°C /10-95% RH
Storage Temp/Hum	-30°C ~ +80°C /10-95% RH
Vibration Resistant	5.9G (ISO 16750.3)
Ingress Protection	ІР69К
ELECTRICAL	·
Power	10 - 32V DC, 150mA
Power & Video Connector	4PIN Aviation options
MECHANICAL	· · ·
Colour/Material	Black, Metal
Weight	355g (V), 470g (S & L)
Dimensions (W x H)	97.5*67.3*66.5 mm (V), 97.5*75.3*72 mm (S & L)
CERTIFICATION	
CE/UKCA IP69K	

Customers who bought our External Box Cameras also viewed:



Stortech IP Micro-Dome Series

- SNV-20XX0C/FS •
- SNV-20XX0C/FAS .
- SNV-20XX0T/FS



Stortech Hybrid Mobile Recorder

- SRH-04020/MW
- SRH-08020/MW
- SMF-0730/WH



Stortech Driver Monitoring Camera

SCH-2028C/I .

Stortech Electronics Ltd

Unit 2, Spire Green Centre, Pinnacles, Harlow, Essex CM19 5TQ

+44 (0) 1279 451100

www.stortech.co.uk sales@stortech.co.uk



Stortech Electronics Ltd



Whilst every effort has been made to ensure the accuracy of the information provided, no liability can be undertaken for any errors or omissions. All dimensions stated in this document are approximate. Stortech Electronics Ltd reserves the right to alter the specifications and introduce changes without prior notice. © Stortech Electronics 2023