# **Mobile Display Monitor**



SMF-0730/ Series



# SMF-0730 Series

7" 3 Channel Input Onboard Display Monitor

CE R

## **Key Features**

- SD and AHD Options
- 7" Screen Size
- Full Screen Display
- 3 Channel Camera Input
- 2 Way Audio
- OSD with Remote Control
- Touch Button Control (SMF-730/HT)
- Weatherproof IP68 (SMF-730/WH)

## **Ordering Information**

SMF-0530/A Stortech, 7", 3Ch input, Full Screen Monitor SMF-0530/HT Stortech, 7", HD, 3Ch, Full Screen Monitor, Touch Screen

SMF-0530/WH Stortech, 7", HD, 3Ch, Full Screen Monitor Weatherproof

## Customers who bought our External Box Cameras also viewed:



### Stortech IP Micro-Dome Series:

- SNV-20XX0C/FS
- SNV-20XX0C/FAS
- SNV-20XX0T/FS



### Stortech 5" On-board Monitors:

- SMF-0530/A
- SMF-0530/H



#### **Stortech Miniature Cameras:**

- MPC-AHD
- MCC-1
- DCC1-AHD-RT

Whilst every effort has been made to ensure the accuracy of the information provided, no liability can be undertaken for any errors or omissions. All dimensions stated in this document are approximate. Stortech Electronics Ltd reserves the right to alter the specifications and introduce changes without prior notice. © Stortech Electronics 2023



## **Specifications**

#### SMF-0730/ Series

MONITOR	
LCD Size	7"
Resolution	800(H) x 600 (V)
Active Display Area	108 x 64.8
Contrast	500:1
Maximum Brightness	450 cd/ m2
Response Time	10 – 15ms
Start-Up Time	2 sec
Viewing Angle	Hor. L (85) R (85) Ver. UP (85) Down (85)
Video Compatibility	PAL / NTSC auto-switching
Video Input	3 - Channel Supporting
Video Resolution	1080P, 720P, 960H, CVBS (25 fps)
Video Display	Full Screen (Single image), Trigger Switching
Aspect Ratio	16:9
Number of Speakers	1 x Built-in
Audio Inputs	2 x One-way input Ch1 & Ch2 (SMF-0730/A & HT only)
Volume Control	± Power On/Off
Speaker Output and	32W x 2W (SMF-0730/A & HT only)
Consumption	
OSD Controls	Contrast, Brightness, reversing delay, image mode, system settings, multi-
	languages
Remote Control	Full-functional
Video Connections	RCA / 4pin connector (Optional)
Mounting Bracket	Yes, (U shade for standard)
Parking Guidelines	On/Off, trigger delay per channel
ENVIRONMENTAL	
Shockproof level	4G
Ingress Protection	IP68 (SMF-0730/WH only)
Operating Temperature	-20°C - +70°C, RH70%
Storage Temperature	-30°C - +85°C, RH70%
ELECTRICAL	
Power Input	10 – 24V DC
Power Consumption	500mA
Power Interface	1 x DC in
MECHANICAL	
Materials	Plastic & With Black Rubber Painted
Dimensions (W x H x D)	207 x 134 x 74.39 mm (730/A & HT) / 208 x 153 x 68mm (730/WH)
Weight	1.0Kg (Net), 1.1kg (Gross)

#### **Stortech Electronics Ltd**

Unit 2, Spire Green Centre, Pinnacles, Harlow, Essex CM19 5TQ

#### +44 (0) 1279 451100

www.stortech.co.uk sales@stortech.co.uk in Stortech Electronics Ltd





Whilst every effort has been made to ensure the accuracy of the information provided, no liability can be undertaken for any errors or omissions. All dimensions stated in this document are approximate. Stortech Electronics Ltd reserves the right to alter the specifications and introduce changes without prior notice. © Stortech Electronics 2023