Onboard 05" Mobile Display Monitor
SMQ-0540/A

stortech | Components and CCTV Specialist

SMQ-0540/A
5" 4-Channel Input Quad Display

CE | UKCA

Key Features

- 5" Screen
- 800 x 480 Resolution
- Quad Screen Display
- 4-Channel Camera Input
- 1-Way Audio
- 16:9 Aspect Radio

Ordering Information
SMQ-0540/A Stortech, 5", 4Ch input, Quad Monitor

Customers who bought our Monitor Range also viewed:

Stortech IP Micro-Domes
- SNV-20XX0C/FS
- SNV-20XX0C/FAS
- SNV-20XX0T/FS

Stortech 7" On-board Monitors
- SMF-0730/A
- SMF-0730/HT
- SMF-0730/WH

Stortech Vandal Wedge Cameras
- RV07 AHD Range
- MPE AHD Range
- MPW AHD Range

Specifications

SMQ-0540/A

MONITOR	
LCD Size	5"
Resolution	800 (H) x 480 (V)
Active Display Area	108 x 64.8
Contrast	500:1
Maximum Brightness	300 cd/m2
Response Time	10 - 15ms
Start-up Time	3 sec
Viewing Angle	Hor. L (70) R (70) Ver. UP (50) Down (70)
Video Synchronisation	Yes
Video Compatibility	PAL / NTSC auto-switching
Video Input	4-Channel Supporting
Video Compatibility	CVBS
Video Display	Quad, Dual, Full Screen (Single image), Trigger Switchable, Reversing
Aspect Ratio	16:9
Number of Speakers	1 x Built-in
Audio Inputs	1 x One-way input Ch2
Volume Control	± Power On/Off Incl.
Sound Demodulation	Available
Speaker output & Consumption	32W x 2W
OSD Controls	Contrast, Brightness, Multi-Languages
Remote Control	Full-functional
Video Connections	RCA / 4pin connector (Optional)
Mounting Bracket	Yes, (U shade for standard)
ENVIRONMENTAL	
Shockproof level	4G
Operating Temperature	-20°C - +70°C, RH70%
Storage Temperature	-30°C - +80°C, RH70%
ELECTRICAL	
Power input	10 – 24V DC
Power Interface	1 x DC in
MECHANICAL	
Materials	Plastic & With Black Rubber Painted
Weight	867g with accessories
Dimensions (W x H x D)	141 x 103 x 25 mm (Inc U Shaped bracket)

Stortech Electronics Ltd   Stortech Electronics Ltd