

### SRH-08020 Series

8-Channel Weatherproof Hybrid MDVR




#### Key Features

- 8- Channel 1080P Resolution
- Up to 4 - IP inputs via a SRI-040 (1 by default)
- 25 ips H.264
- SD Card x 1 (512GB), SSD x 1 (2TB) Capacity
- AI Algorithms - Driver Monitoring System / Advanced Driving Assistance System / Driver Assistance System / Blind Spot Detection / Around View Monitoring (360°)
- 8-Audio Inputs
- Automatic Upgrade via USB
- 10 - 32V DC



#### Ordering Information

SRH-08020/MWA 8-Ch, AHD, H.264, AI, 10-32V, RS232/485  
SRI-040 4-Ch, IP camera adapter for SRH recorders



# Specifications

<b>MOBILE RECORDER</b>		<b>SRH-08020/MW Series</b>	
Operating System	Linux		
Operating Interface	Graphical menu operation interface (OSD)		
<b>VIDEO</b>			
Input Resolution	8-Channels, 1080P AHD, additional 1 IP camera input (total of 4 IP inputs via SRI-040)		
CVBS Output	1 Channel 6pin aviation connector output PAL/NSTC		
VGA Output	1 Channel VGA output, 1080P		
Display Mode	Single/Split/Triple/Quad/8 Cam/9 Cam/Black Screen display		
Standard	25fps (PAL)		
Compression	H.264 (Main Profile)		
Bit Rate	64kbps - 4Mbps / Channel		
Streaming	Mainstream (recording), Sub Stream (Network Transmission)		
Algorithms	Driver Monitoring System / Advanced Driving Assistance System / Driver Assistance System / Blind Spot Detection /Around View Monitoring (360°)		
<b>RECORDING/STORAGE</b>			
Storage	56 - 1800MB / Channel/hour, SD card x 1 (512GB), SSD x 1 (2TB) (not included as standard)		
Format	Synchronized video & audio recording		
Modes	Power up, schedule and event recording (G-Sensor recording, Overspeed recording, Motion detection recording, Alarm recording 1-6 and Panic button recording etc.)		
Clock	Built-in, Calendar		
<b>AUDIO</b>			
Input	8 Channels		
Output	2 Channel (CBVS 6pin aviation or HD VGA 1080P) only one can be used		
Compression	ADPCM		
Bit Rate	32kbps		
<b>CONNECTIONS</b>			
Infrared	1 Channel		
RS-232	1 Channel		
RS-485	1 Channel		
CAN	2 Channel		
USB2.0	1 Channel		
RJ45	1 Channel		
2G/3G/4G	Optional		
Wi-Fi	Standard		
Wi-Fi hotspot/AP	Optional		
GPS	Optional		
3-Axis Acceleration Sensor	G-Sensor		
Windows Client	Available		
iOS Client	Available		
Web Portal	Available		
<b>ALARM</b>			
Input	8 Channels		
Output	2 Channels, 1 Buzzer		
Motion Detection	High / Low / off, Sensitivity adjustment		
Support Automatic Uploading	Alarm recording files, alarm information, log information and GPS trajectory		
<b>ENVIROMENTAL</b>			
Operating temperature	20~70 degree/ <80%		
Vibration Rating	MIL-STD-810G		
IP rating	IP69K		

<b>ELECTRICAL</b>	
Power	10 - 32V DC / 12V DC @ 4A
Current Consumption	48W
<b>MECHANICAL</b>	
Colour / Material	Black / Metal
Cable Length	38cm
Dimensions (W x H)	342*194*100mm
Weight	3.1kg
<b>CERTIFICATION</b>	
CE / UKCA	

**Customers who bought our External Box Cameras also viewed:**



**Stortech Driver Monitoring Camera:**

- SHC-20280C/I



**Stortech 360° 7" Vehicle Monitoring System**

- SMF-0740/360H



**Stortech IP Micro-Dome Series**

- SNV-20XX0C / FS
- SNV-20XX0C / FAS
- SNV-20XX0T / FS

**Stortech Electronics Ltd**

Unit 2, Spire Green Centre, Pinnacles,  
Harlow, Essex  
CM19 5TQ

+44 (0) 1279 451100

[www.stortech.co.uk](http://www.stortech.co.uk)   [sales@stortech.co.uk](mailto:sales@stortech.co.uk)



Stortech Electronics Ltd



Stortech Electronics Ltd